



California Building Materials Supply
Sales@EarthStoneRock.com
800 215 7372|626 263 0531



EarthStoneRock.com

4408 Vahan Court, Lancaster, CA 93536

BocceCourtPro.com

Black Pearl Bocce Blends

Traditionally Bocce Ball courts are covered with a 2 to 3-inch layer of crushed oyster flour spread that has been blended with decomposed granite in a very fine 1/4" minus screen size. In regions with high spring and summer rainfall, it is advisable to use a greater percentage of oyster flour and washed concrete sand for improved drainage and ease of maintenance. After the installation of the playing surface has been done a layer of finely crushed oyster shell flour is often applied. We supply all of these materials for court installations and for seasonal maintenance.

The role that oyster flour plays in bocce court surface mixtures is to keep the decomposed granite from binding together becoming extremely hard and un-workable for grooming. The oyster flour flakes keep the decomposed granite from completely binding together. Through the normal course of play; ruts, troughs, and material displacement takes place. Our decomposed granite oyster flour blend is in the traditional Italian bocce ball court surface formula. When groomed out it makes a smooth solid surface to play on. When play is completed it makes for an easy surface to quickly renovate.

We offer several different surface material options, with and without an oyster flour.

Our Wet Climate or Rain Country Blend has a higher percentage of oyster flour and washed concrete sand for increase drainage.

We are also able to ship all of the other materials needed for installation and maintenance to you.

Installation and maintenance services are available. Our staff is available with free rental tools to assist you or your contractor with an installation.

Black Hawk Decomposed Granite 3/8" Minus

SIEVE SIZE	PASSING %
75-mm (3")	X
50-mm (2")	X
37.5-mm (1.5")	X
25.0-mm (1")	X
19.0-mm (3/4")	X
12.5-mm (1/2")	X
9.5-mm (3/8")	100
4.75-mm (#4)	95
2.36-mm (#8)	74
1.18-mm (#16)	59
600-µm (#30)	46
300-µm (#50)	31
150-µm (#100)	19
75-µm (#200)	9



INSTALLATION INSTRUCTIONS

Make sure court drains satisfactory and existing grade is compacted and leveled prior to installing

A APPLY

- 1 Spread a 2"- 3" layer of our Bocce Court Pro Mix




- 2 Level Bocce Court Pro Mix using a rake of size 44"- 48"



- 3 Thoroughly Saturate Bocce Court Pro Mix surface with Water


(Note: You cannot over water)



B COMPACT

Drum Roller:

The Bocce Court Pro Mix surface must then be compacted using a roller



C OYSTER SHELL FLOUR



After compaction of the Bocce Court Pro Mix surface spread the Oyster Shell Flour on top at a depth of 1/4" to 1/2"


D PREPERATION

Water the Bocce Court Pro Mix surface to remove compaction lines.




E MAINTENANCE

- 1 Water the Bocce Court Pro Mix surface using a hose nozzle for a 1/4" depth penetration



- 2 Spike drag the surface at 1/8" depth using spike drag.

(This will take out marks left by balls after play)



- 3 Water the Bocce Court Pro Mix Surface.

